



Wheel Fitment Guide

2008

IMPORTANT WHEEL GUIDE INFORMATION

PLEASE READ!

This guide is presented as a general sales and reference guideline for M/T Wheels ONLY. These suggestions are a starting point only and all fitment should be checked prior to mounting tires on wheels. These suggestions in no way express or imply safety or fitness of the vehicle or the minimum changes which may be required to install M/T Wheels.

All Wheel Lug Nuts Must Be Re-torqued After Driving The Vehicle 100 Miles.

CAUTION!

If changing the overall tire diameter from the original, the speedometer accuracy and anti-lock brake system (ABS) may be affected, as well as automatic transmission shift points.

CAUTION!

Vehicles should not be fitted with smaller diameter wheels than the original equipment wheels as resulting clearance issues may arise due to diameter/offset changes. Always test fit wheels for clearance before mounting tires.

LIMITED LIFETIME WARRANTY

Mickey Thompson Performance Tires warrants to the original purchaser that a new M/T Wheel is free from defects in material and workmanship and agrees to replace a M/T Wheel which fails in normal use and service resulting from defects in material and workmanship for the life of the vehicle for which said wheel was intended and purchased for. Mickey Thompson Performance Tires does not warrant any wheel which has been subject to misuse or abuse including the following; (a) Using tires which are oversized according to the standards recommended by the Tire and Rim Association, Inc.; (b) Loading the wheel beyond the applicable maximum wheel load as specified by Mickey Thompson Performance Tires; (c) Any type of racing or activity which subjects wheels to the abuse of racing, whether on the road or off; (d) Inflating beyond the maximum specified on any given tire size as specified by Mickey Thompson Performance Tires; (e) Changing or altering the original condition of the wheel or by subjecting it to any processing such as welding or straightening.

THERE IS NO WARRANTY THAT WHEELS ARE MERCHANTABLE OR SATISFACTORY FOR ANY PARTICULAR PURPOSE NOR IS THERE ANY OTHER WARRANTY EXPRESSED OR IMPLIED EXCEPT AS SET FORTH HEREIN. Mickey Thompson Performance Tires shall not be liable for any incidental or consequential damages for any breach of warranty, its liability and the purchaser's exclusive remedy being expressly limited to replacement of defective wheel, as herein provided. Replacement will be handled by an authorized Mickey Thompson Performance Tire Dealer or Mickey Thompson Performance Tire representative.

This warranty gives you specific legal rights. You may also have other rights under applicable laws.

Vehicle	Bolt Pattern	15x8	15x10	15x12	16x8	16x10	16x12	16.5x9.75	16.5x12	17x9	18x9	18x10	20x9	20x10
CHEVY/GMC														
89 - 04 Geo Tracker	5 on 5 1/2	358401 458401	-	-	368401 468401	-	-	-	-	379402 479402	-	-	-	-
82 - 04 S/T Series Truck's, SUV's	5 on 4 3/4	358441	-	-	-	-	-	-	-	-	-	-	-	-
04 - 08 Colorado and GMC Canyon (All except Sport)	6 on 5 1/2	-	-	-	368411 368412^ 468412^	360411 360412^ 460412^	-	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
04 - 08 Colorado - Sport	6 on 5 1/2	-	-	-	-	-	-	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
73 - 91 K-5 Blazer, Jimmy, Suburban 1/2 Ton 4WD	6 on 5 1/2	358411 458411	350411 450411A	352411	368412^ 468412^	-	-	-	-	379412^ 479412^	389413^	480412^	329413^	-
73 - 91 C10 Truck, Blazer, Suburban 2WD	5 on 5	358431	-	-	-	-	-	-	-	379431 479431	389431	-	-	-
92 - 99 Blazer, Yukon, Tahoe, Suburban, K1500 4WD	6 on 5 1/2	358411 458411	350411 450411A	352411	368411 368412 468412^	360411 360412^ 460412^	361412^ 461412^	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
88 - 98 C1500 Truck 2WD	5 on 5	358431	-	-	-	-	-	-	-	379431 479431	389431	-	-	-
92 - 99 Blazer, Yukon, Tahoe, Suburban, C1500 2WD	5 on 5	358431	-	-	-	-	-	-	-	379431 479431	389431	-	-	-
88 - 98 K1500 Truck 4WD	6 on 5 1/2	358411 458411	350411 450411A	352411	368411 368412^ 468412^	360411 360412^ 460412^	361412^ 461412^	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
73 - 87 K-10 Truck 4WD	6 on 5 1/2	358411 458411	350411 450411A	352411	368412^ 468412^	-	-	-	-	379412^ 479412^	389413^	480412^	329413^	-

Mickey Thompson Performance Tires & Wheels recommends standard 'bulge' acorn lug nuts (conical seat) on all Classic II and Classic Lock Wheel and duplex 'bulge' acorns on vehicles with a GVWR of 6500lbs or greater.

Footnotes:

* = Hub centric application - wheel includes fitment ring.

** = Hub centric factory recommended - wheel will be centered on lug nuts.

^ = Included hub centering ring is not needed for this application, please discard.
Included center cap will not work on manual hub applications.

= Some 3/4 ton and 1 ton vehicles use extra long center caps,
we recommend using the M/T optional aluminum caps (sold separately).

Vehicle	Bolt Pattern	15x8	15x10	15x12	16x8	16x10	16x12	16.5x9.75	16.5x12	17x9	18x9	18x10	20x9	20x10
CHEVY/GMC														
99 - 04 Silverado / Sierra 1500 2WD / 4WD	6 on 5 1/2	-	-	-	368412* 468412*	360412* 460412*	361412* 461412*	-	-	379412* 479412*	389413*	480412*	329413*	-
05 - 08 Silverado / Sierra 1500 2WD / 4WD	6 on 5 1/2	-	-	-	-	-	-	-	-	379412* 479412*	389413*	480412*	329413*	-
00 - 04 Tahoe, Yukon, Yukon XL 1500, Denali 2WD / 4WD	6 on 5 1/2	-	-	-	368412* 468412*	360412* 460412*	361412* 461412*	-	-	379412* 479412*	389413*	480412*	329413*	-
05 - 08 Tahoe, Yukon, Yukon XL 1500, Denali 2WD / 4WD	6 on 5 1/2	-	-	-	-	-	-	-	-	379412* 479412*	389413*	480412*	329413*	-
01 - 04 1500 Avalanche	6 on 5 1/2	-	-	-	368412* 468412*	360412* 460412*	361412* 461412*	-	-	379412* 479412*	389413*	480412*	329413*	-
05 - 08 1500 Avalanche	6 on 5 1/2	-	-	-	-	-	-	-	-	379412* 479412*	389413*	480412*	329413*	-
73 - 87 C/K 20 & 30 Series Truck 2WD / 4WD	8 on 6 1/2	-	-	-	368482# 468482#	360481# 460481#	361481# 461481#	365482#	362481#	379481# 479481#	389483#	480481#	329483#	420481#
88 - 98 C2500/C3500 Truck	8 on 6 1/2	-	-	-	368482 468482	360481 460481	-	365482	-	379481 479481	389483	480481	329483	420481#
88 - 98 K2500 / K3500 Truck 4WD	8 on 6 1/2	-	-	-	368482 468482	360481 460481	361481# 461481#	365482	362481	379481 479481	389483	480481	329483	420481
73 - 91 3/4 Ton Suburban 2WD/4WD	8 on 6 1/2	-	-	-	368482# 468482#	360481# 460481#	-	365482#	-	379481# 479481#	389483#	480481#	329483#	420481#
92 - 99 Suburban C/K 2500 2WD / 4WD	8 on 6 1/2	-	-	-	368482 468482	360481 460481	361481# 461481#	365482	362481	379481 479481	389483	480481	329483	420481

Mickey Thompson Performance Tires & Wheels recommends standard 'bulge' acorn lug nuts (conical seat) on all Classic II and Classic Lock Wheel and duplex 'bulge' acorns on vehicles with a GVWR of 6500lbs or greater.

Footnotes:

* = Hub centric application - wheel includes fitment ring.

** = Hub centric factory recommended - wheel will be centered on lug nuts.

^ = Included hub centering ring is not needed for this application, please discard.

Included center cap will not work on manual hub applications.

= Some 3/4 ton and 1 ton vehicles use extra long center caps, we recommend using the M/T optional aluminum caps (sold separately).

Vehicle	Bolt Pattern	15x8	15x10	15x12	16x8	16x10	16x12	16.5x9.75	16.5x12	17x9	18x9	18x10	20x9	20x10
CHEVY/GMC														
99 - 04 Silverado / Sierra 1500HD, 2500, 3500 Yukon XL/HD, Suburban HD 2WD / 4WD	8 on 6 1/2	-	-	-	368482** 468482**	360481** 460481**	361481** 461481**	365482**	362481**	379481** 479481**	389483**	480481**	329483**	420481**
05 - 08 Silverado / Sierra 1500HD, 2500, 3500 Yukon XL/HD, Suburban HD 2WD / 4WD	8 on 6 1/2	-	-	-	-	-	-	-	-	379481** 479481**	389483**	480481**	329483**	420481**
02 - 08 2500 Avalanche	8 on 6 1/2	-	-	-	368482** 468482**	360481** 460481**	361481** 461481**	365482**	362481**	379481** 479481**	389483**	480481**	329483**	420481**
03 - 08 Hummer - H2	8 on 6 1/2	-	-	-	368482** 468482**	360481** 460481**	361481** 461481**	365482**	362481**	379481** 479481**	389483**	480481**	329483**	420481**
06 - 08 Hummer - H3	6 on 5 1/2	-	-	-	368411 368412^ 468412^	360411 360412^ 460412^	-	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
2001 G10 Van	5 on 5	358431	-	-	-	-	-	-	-	379431	-	-	-	-
2001 G20 Light Duty Express Van	6 on 5 1/2	-	-	-	368411 368412^ 468412^	-	-	-	-	379412^ 479412^	389413^	480412^	329413^	-
2001 G20/G30 Van	8 on 6 1/2	-	-	-	368482 468482	-	-	365482	-	379481 479481	389483	480481	329483	420481
DAIHATSU														
82 - 91 Rocky	5 on 5 1/2	358401 458401	-	-	368401 468401	-	-	-	-	379402 479402	-	-	-	-

Mickey Thompson Performance Tires & Wheels recommends standard 'bulge' acorn lug nuts (conical seat) on all Classic II and Classic Lock Wheel and duplex 'bulge' acorns on vehicles with a GVWR of 6500lbs or greater.

Footnotes:

* = Hub centric application - wheel includes fitment ring.

** = Hub centric factory recommended - wheel will be centered on lug nuts.

^ = Included hub centering ring is not needed for this application, please discard.

Included center cap will not work on manual hub applications.

= Some 3/4 ton and 1 ton vehicles use extra long center caps, we recommend using the M/T optional aluminum caps (sold separately).

Vehicle	Bolt Pattern	15x8	15x10	15x12	16x8	16x10	16x12	16.5x9.75	16.5x12	17x9	18x9	18x10	20x9	20x10
DODGE														
87 - 91 Raider / D50 4WD	6 on 5 1/2	358411 458411	-	-	368411 368412^ 468412^	-	-	-	-	379411 379412^ 479412^	-	-	-	-
87 - 90 Dakota 2WD / 4WD	5 on 4 1/2	358421 458421	350421 450421A	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
05 - 08 Dakota	5 on 5 1/2	-	-	-	-	-	-	-	-	379402 479402	-	480402	-	-
04 - 08 Durango	5 on 5 1/2	-	-	-	-	-	-	-	-	379402 479402	-	480402	-	-
07 - 08 Nitro	5 on 4 1/2	-	-	-	368421 468421	-	-	-	-	379421 479421	-	-	-	-
74 - 84 1/2 Ton Truck & Ramcharger 4WD	5 on 4 1/2	358421 458421	350421 450421A	-	-	-	-	-	-	379421 479421	-	380421	-	-
74 - 84 1/2 Ton Truck & Ramcharger 2WD	5 on 4 1/2	358421 458421	350421 450421A	-	368421 468421	-	-	-	-	379421 479421	-	380421	-	-
80 - 93 1/2 Ton Truck, Ramcharger 4WD with manual hubs	5 on 5 1/2	358401 458401	350401 450401A	352401	-	-	-	-	-	379402 479402	-	480402	-	-
85 - 93 1/2 Ton Truck, Ramcharger 2WD	5 on 5 1/2	358401 458401	350401 450401A	-	368401 468401	360401 460401	-	-	-	379402 479402	-	480402	-	-
46 - 93 3/4 Ton, 1Ton Truck 2WD / 4WD	8 on 6 1/2	-	-	-	368482# 468482#	360481# 460481#	361481# 461481#	365482#	362481#	379481# 479481#	389483#	480481#	329483#	420481#
94 - 01 Ram 1500 Truck 2WD / 4WD	5 on 5 1/2	358401 458401	350401 450401A	352401	368401 468401	360401 460401	-	-	-	379402 479402	-	480402	-	-
02 - 08 Ram 1500 Truck 2WD / 4WD (Except Mega Cab)	5 on 5 1/2	-	-	-	-	-	-	-	-	379402 479402	-	480402	-	-

Mickey Thompson Performance Tires & Wheels recommends standard 'bulge' acorn lug nuts (conical seat) on all Classic II and Classic Lock Wheel and duplex 'bulge' acorns on vehicles with a GVWR of 6500lbs or greater.

Footnotes:

* = Hub centric application - wheel includes fitment ring.

** = Hub centric factory recommended - wheel will be centered on lug nuts.

^ = Included hub centering ring is not needed for this application, please discard.
Included center cap will not work on manual hub applications.

= Some 3/4 ton and 1 ton vehicles use extra long center caps,
we recommend using the M/T optional aluminum caps (sold separately).

Vehicle	Bolt Pattern	15x8	15x10	15x12	16x8	16x10	16x12	16.5x9.75	16.5x12	17x9	18x9	18x10	20x9	20x10
DODGE														
94 - 01 Ram 2500 & 3500 Truck 2WD / 4WD	8 on 6 1/2	-	-	-	368482 468482	360481 460481	361481 461481	365482	362481	379481 479481	389483#	480481	329483#	420481
02 - 08 Ram 2500 & 3500 Truck 2WD / 4WD 1500 Mega Cab	8 on 6 1/2	-	-	-	-	-	-	-	-	379481 479481	389483#	480481	329483#	420481
74 - 84 1/2 Ton Van	5 on 4 1/2	358421 458421	-	-	368421 468421	-	-	-	-	379421 479421	-	380421	-	-
85 - 93 1/2 Ton Van	5 on 5 1/2	358401 458401	-	-	368401 468401	-	-	-	-	379402 479402	-	480402	-	-
3/4 & 1Ton Van & Ram Wagon	8 on 6 1/2	-	-	-	368482# 468482#	-	-	-	-	379481# 479481#	389483#	480481#	329483#	420481#
FORD														
83 - 92 Ranger, Bronco II 2WD / 4WD	5 on 4 1/2	358421 458421	350421 450421A	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
93 - 08 Ranger 2WD / 4WD	5 on 4 1/2	358421 458421	350421 450421A	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
01 - 08 Escape	5 on 4 1/2	358421 458421	-	-	368421 468421	-	-	-	-	379421 479421	-	-	-	-
91 - 01 Explorer, Mercury Mountaineer	5 on 4 1/2	358421 458421	350421 450421A	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
02 - 08 Explorer, Mercury Mountaineer	5 on 4 1/2	-	-	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
02 - 08 Mercury Mountaineer	5 on 4 1/2	-	-	-	-	-	-	-	-	379421 479421	-	380421	-	-

Mickey Thompson Performance Tires & Wheels recommends standard 'bulge' acorn lug nuts (conical seat) on all Classic II and Classic Lock Wheel and duplex 'bulge' acorns on vehicles with a GVWR of 6500lbs or greater.

Footnotes:

* = Hub centric application - wheel includes fitment ring.

** = Hub centric factory recommended - wheel will be centered on lug nuts.

^ = Included hub centering ring is not needed for this application, please discard.

Included center cap will not work on manual hub applications.

= Some 3/4 ton and 1 ton vehicles use extra long center caps, we recommend using the M/T optional aluminum caps (sold separately).

Vehicle	Bolt Pattern	15x8	15x10	15x12	16x8	16x10	16x12	16.5x9.75	16.5x12	17x9	18x9	18x10	20x9	20x10
FORD														
03 - 05 Lincoln Aviator	5 on 4 1/2	-	-	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
05 - 06 Mercury Mariner	5 on 4 1/2	-	-	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
01 - 08 Explorer Sport-Trac	5 on 4 1/2	-	-	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
66 - 79 Bronco	5 on 5 1/2	358401 458401	350401 450401A	352401	-	-	-	-	-	379402 479402	-	480402	-	-
80 - 96 Bronco	5 on 5 1/2	358401 458401	350401 450401A	352401	368401 468401	360401 460401	-	-	-	379402 479402	-	480402	-	-
65 - 79 F-100, 150 2WD / 4WD	5 on 5 1/2	358401 458401	350401 450401A	352401	-	-	-	-	-	379402 479402	-	480402	-	-
80 - 96 F-150 2WD / 4WD	5 on 5 1/2	358401 458401	350401 450401A	352401	368401 468401	360401 460401	-	-	-	379402 479402	-	480402	-	-
94 - 96 F-150 Lightning Truck	5 on 5 1/2	-	-	-	-	-	-	-	-	379402 479402	-	480402	-	-
97 - 03 F-150 2WD / 4WD	5 on 135mm	-	-	-	368452**	360452**	-	-	-	379452** 479452**	-	-	-	-
97 - 02 Expedition / Navigator 2WD / 4WD	5 on 135mm	-	-	-	368452**	360452**	-	-	-	379452** 479452**	-	-	-	-
03 - 08 Expedition	6 on 135mm	-	-	-	-	-	-	-	-	379462** 479462**	-	480462**	-	320462**
03 - 08 Navigator 2WD / 4WD	6 on 135mm	-	-	-	-	-	-	-	-	-	-	480462**	-	320462**
97 - 03 F-150 Lightning / Harley Davidson Truck	5 on 135mm	-	-	-	-	-	-	-	-	379452** 479452**	-	-	-	-
04 - 08 F150 2WD / 4WD	6 on 135mm	-	-	-	-	-	-	-	-	379462** 479462**	-	480462**	-	320462**

Mickey Thompson Performance Tires & Wheels recommends standard 'bulge' acorn lug nuts (conical seat) on all Classic II and Classic Lock Wheel and duplex 'bulge' acorns on vehicles with a GVWR of 6500lbs or greater.

Footnotes:

* = Hub centric application - wheel includes fitment ring.

** = Hub centric factory recommended - wheel will be centered on lug nuts.

^ = Included hub centering ring is not needed for this application, please discard.
Included center cap will not work on manual hub applications.

= Some 3/4 ton and 1 ton vehicles use extra long center caps,
we recommend using the M/T optional aluminum caps (sold separately).

Vehicle	Bolt Pattern	15x8	15x10	15x12	16x8	16x10	16x12	16.5x9.75	16.5x12	17x9	18x9	18x10	20x9	20x10
FORD														
48 - 97 F-250, F-350 2WD / 4WD	8 on 6 1/2	-	-	-	368482# 468482#	360481# 460481#	361481# 461481#	365482#	362481#	379481# 479481#	389483#	480481#	329483#	420481#
48 - 97 F-250, F-350 2WD / 4WD w/Dana 60	8 on 6 1/2	-	-	-	368482# 468482#	360481# 460481#	361481# 461481#	365482#	362481#	379481# 479481#	389483#	480481#	329483#	420481#
98 - 04 F250 & F350 Superduty 2WD / 4WD	8 on 170mm	-	-	-	368170**# 468170**#	360170**# 460170**#	361170**# 461170**#	365170**#	362170**#	379170**# 479170**#	389173**#	480170**#	329173**#	420170**#
05 - 08 F250 & F350 Superduty 2WD / 4WD	8 on 170mm	-	-	-	-	-	-	-	-	379170**# 479170**#	389173**#	480170**#	329173**#	420170**#
00 - 05 Excursion 2WD / 4WD	8 on 170mm	-	-	-	368170**# 468170**#	360170**# 460170**#	361170**# 461170**#	365170**#	362170**#	379170**# 479170**#	389173**#	480170**#	329173**#	420170**#
48 - 06 E250 & E350 Van	8 on 6 1/2	-	-	-	368482# 468482#	360481# 460481#	-	365482#	-	379481# 479481#	389483#	480481#	329483#	420481#
HONDA/ ISUZU														
83 - 95 Isuzu Pickup	6 on 5 1/2	358411 458411	350411 450411A	-	368411 368412^ 468412^	360411 460412^	-	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
84 - 99 Isuzu Amigo 98 - 99 Isuzu Rodeo 84 - 99 Isuzu Trooper II	6 on 5 1/2	358411 458411	350411 450411A	-	368411 368412^ 468412^	360411 460412^	-	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
97 - 02 Honda Passport 00 - 04 Isuzu Rodeo	6 on 5 1/2	358411 458411	-	-	368411 368412^ 468412^	-	-	-	-	379411 379412^ 479412^	-	-	-	-
2000 Isuzu Amigo 97 - 02 Isuzu Trooper 97 - 99 Acura SLX	6 on 5 1/2	-	-	-	368411 368412^ 468412^	-	-	-	-	379411 379412^ 479412^	-	-	-	-
96 - 00 Isuzu Hombre	6 on 5 1/2	358411 458411	-	-	368411 368412^ 468412^	-	-	-	-	379411 379412^ 479412^	-	-	-	-
03 - 08 Honda Pilot	5 on 4 1/2	-	-	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-

Mickey Thompson Performance Tires & Wheels recommends standard 'bulge' acorn lug nuts (conical seat) on all Classic II and Classic Lock Wheel and duplex 'bulge' acorns on vehicles with a GVWR of 6500lbs or greater.

Footnotes:

* = Hub centric application - wheel includes fitment ring.

** = Hub centric factory recommended - wheel will be centered on lug nuts.

^ = Included hub centering ring is not needed for this application, please discard.

Included center cap will not work on manual hub applications.

= Some 3/4 ton and 1 ton vehicles use extra long center caps, we recommend using the M/T optional aluminum caps (sold separately).

Vehicle	Bolt Pattern	15x8	15x10	15x12	16x8	16x10	16x12	16.5x9.75	16.5x12	17x9	18x9	18x10	20x9	20x10
JEEP														
06-08 Commander	5 on 5	-	-	-	-	-	-	-	-	379431 479431	389431	-	-	-
07 - 08 Compass	5 on 4 1/2	-	-	-	368421 468421	-	-	-	-	379421 479421	-	-	-	-
93 - 98 Grand Cherokee	5 on 4 1/2	358421 458421	350421 450421A	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
99 - 08 Grand Cherokee	5 on 5	-	-	-	-	-	-	-	-	379431 479431	389431	-	-	-
07 - 08 Patriot	5 on 4 1/2	-	-	-	368421 468421	-	-	-	-	379421 479421	-	-	-	-

Mickey Thompson Performance Tires & Wheels recommends standard 'bulge' acorn lug nuts (conical seat) on all Classic II and Classic Lock Wheel and duplex 'bulge' acorns on vehicles with a GVWR of 6500lbs or greater.

Footnotes:

* = Hub centric application - wheel includes fitment ring.

** = Hub centric factory recommended - wheel will be centered on lug nuts.

^ = Included hub centering ring is not needed for this application, please discard.
Included center cap will not work on manual hub applications.

= Some 3/4 ton and 1 ton vehicles use extra long center caps,
we recommend using the M/T optional aluminum caps (sold separately).

Vehicle	Bolt Pattern	15x8	15x10	15x12	16x8	16x10	16x12	16.5x9.75	16.5x12	17x9	18x9	18x10	20x9	20x10
JEEP														
87 - 96 Wrangler YJ	5 on 4 1/2	358421 458421	350421 450421A	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
97 - 06 Wrangler TJ	5 on 4 1/2	358421 458421	350421 450421A	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
07 - 08 Wrangler JK	5 on 5	-	-	-	-	-	-	-	-	379431 479431	389431	-	-	-
84 - 01 Cherokee, Comanche	5 on 4 1/2	358421 458421	350421 450421A	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
02 - 08 Liberty	5 on 4 1/2	-	-	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
82 - 86 CJ 5, 7, 8 With "Wide Track Front End"	5 on 5 1/2	358401 458401	350401 450401A	352401	-	-	-	-	-	379402 479402	-	480402	-	-
55 - 82 CJ 5, 7, 8 With "Narrow Track Front End"	5 on 5 1/2	358401 458401	350401 450401A	352401	-	-	-	-	-	379402 479402	-	480402	-	-
74 - 91 J10, Wagoneer Fullsize	6 on 5 1/2	358411 458411	350411 450411A	352411	368412^ 468412^	-	-	-	-	379412^ 479412^	389413^	480412^	329413^	-
74 - 88 J20 Truck	8 on 6 1/2	-	-	-	368482# 468482#	360481# 460481#	361481#	365482#	362481#	379481# 479481#	389483#	480481#	329483#	420481#

Mickey Thompson Performance Tires & Wheels recommends standard 'bulge' acorn lug nuts (conical seat) on all Classic II and Classic Lock Wheel and duplex 'bulge' acorns on vehicles with a GVWR of 6500lbs or greater.

Footnotes:

* = Hub centric application - wheel includes fitment ring.

** = Hub centric factory recommended - wheel will be centered on lug nuts.

^ = Included hub centering ring is not needed for this application, please discard.

Included center cap will not work on manual hub applications.

= Some 3/4 ton and 1 ton vehicles use extra long center caps, we recommend using the M/T optional aluminum caps (sold separately).

Vehicle	Bolt Pattern	15x8	15x10	15x12	16x8	16x10	16x12	16.5x9.75	16.5x12	17x9	18x9	18x10	20x9	20x10
MAZDA														
77 - 94 Pickup 2WD / 4WD	6 on 5 1/2	358411 458411	-	-	368411 368412^ 468412^	360412^ 460412^	-	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
95 - 07 Pickup 2WD / 4WD	5 on 4 1/2	358421 458421	350421 450421A	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
91 - 94 Navajo	5 on 4 1/2	358421 458421	350421 450421A	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
01 - 08 Tribute	5 on 4 1/2	-	-	-	368421 468421	-	-	-	-	379421 479421	-	-	-	-
MITSUBISHI														
83 - 96 Pickup 2WD / 4WD	6 on 5 1/2	358411 458411	-	-	368411 368412^ 468412^	360412^ 460412^	-	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
04 - 08 Endeavor	5 on 4 1/2	-	-	-	-	-	-	-	-	379421 479421	-	-	-	-
84 - 04 Montero (Pajero)	6 on 5 1/2	358411 458411	-	-	368411 368412^ 468412^	360412^ 460412^	-	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
05 - 06 Montero (Pajero)	6 on 5 1/2	-	-	-	-	-	-	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
06 - 08 Raider	5 on 5 1/2	-	-	-	368401 468401	360401 460401	-	-	-	379402 479402	-	480402	-	-

Mickey Thompson Performance Tires & Wheels recommends standard 'bulge' acorn lug nuts (conical seat) on all Classic II and Classic Lock Wheel and duplex 'bulge' acorns on vehicles with a GVWR of 6500lbs or greater.

Footnotes:

* = Hub centric application - wheel includes fitment ring.

** = Hub centric factory recommended - wheel will be centered on lug nuts.

^ = Included hub centering ring is not needed for this application, please discard.
Included center cap will not work on manual hub applications.

= Some 3/4 ton and 1 ton vehicles use extra long center caps, we recommend using the M/T optional aluminum caps (sold separately).

Vehicle	Bolt Pattern	15x8	15x10	15x12	16x8	16x10	16x12	16.5x9.75	16.5x12	17x9	18x9	18x10	20x9	20x10
NISSAN														
78 - 86 Pickup 2WD / 4WD	6 on 5 1/2	358411 458411	350411 450411A	-	368411 368412^ 468412^	360411 360412^ 460412^	-	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
87 - 97 Hardbody Pickup 2WD / 4WD	6 on 5 1/2	358411 458411	350411 450411A	-	368411 368412^ 468412^	360411 360412^ 460412^	-	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
00 - 04 Frontier Truck	6 on 5 1/2	358411 458411	350411 450411A	-	368411 368412^ 468412^	360411 360412^ 460412^	-	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
04 - 08 Titan	6 on 5 1/2	-	-	-	-	-	-	-	-	-	389413^	-	329413^	-
SUZUKI														
86 - 91 Samurai	5 on 5 1/2	358401 458401	350401 450401A	-	-	-	-	-	-	379402 479402	-	480402	-	-
89 - 00 Sidekick	5 on 5 1/2	358401 458401	-	-	-	-	-	-	-	379402 479402	-	-	-	-

All Classic II and Classic Lock Wheels use standard 'bulge' acorn lug nuts (conical seat). Mickey Thompson Performance Tires & Wheels recommends duplex 'bulge' acorns on vehicles with GVWR of 6500lbs or greater.

Footnotes:

* = Hub centric application - wheel includes fitment ring.

** = Hub centric factory recommended - wheel will be centered on lug nuts.

*** = Caps included may not fit some Toyota center hubs.

^ = Included hub centering ring is not needed for this application, please discard.

Included center cap will not work on manual hub applications.

= Some 3/4 ton and 1 ton vehicles use extra long center caps, we recommend using the M/T optional aluminum caps (sold separately).

Vehicle	Bolt Pattern	15x8	15x10	15x12	16x8	16x10	16x12	16.5x9.75	16.5x12	17x9	18x9	18x10	20x9	20x10
TOYOTA														
84 - 94 Pickup 2WD	5 on 4 1/2	358421 458421	-	-	368421 468421	360421 460421	-	-	-	379421 479421	-	380421	-	-
79 - 94 Pickup 4WD*** and up to 1996 4-Runner***	6 on 5 1/2	358411 458411	350411 450411A	352411	368411 368412^ 468412^	360411 360412^ 460412^	361412^ 461412^	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
01 - 04 Tacoma 4WD Standard Cab 4Cyl. Truck and T-100 Truck***	6 on 5 1/2	358411 458411	350411 450411A	352411	368411 368412^ 468412^	360411 360412^ 460412^	361412^ 461412^	-	-	379411 379412^ 479412^	389413^	480412^	329413^	-
05 - 08 Tacoma All V-6 and Extra-Cab 4cyl., including TRD & Pre-Runner	6 on 5 1/2	-	-	-	-	-	-	-	-	379413^ 479412^	389413^	480412^	329413^	-
75 - 84 FJ40 Landcruiser***	6 on 5 1/2	358411 458411	350411 450411A	352411	368412^	-	-	-	-	379412^ 479412^	389413^	480412^	329413^	-
84 - 92 FJ60 Landcruiser***	6 on 5 1/2	358411 458411	350411 450411A	-	368412^ 468412^	-	-	-	-	379412^ 479412^	389413^	480412^	329413^	-
07 - 08 FJ Cruiser***	6 on 5 1/2	-	-	-	-	-	-	-	-	379413^	389413^	-	329413^	-
00 - 06 Tundra	6 on 5 1/2	-	-	-	368412^ 468412^	360412^ 460412^	361412^ 461412^	-	-	379412^ 479412^	389413^	480412^	329413^	-
07 - 08 Tundra	5X150	-	-	-	-	-	-	-	-	379403	389403	-	329403	-
94 - 97 Land Cruiser	6 on 5 1/2	-	-	-	368412^ 468412^	-	-	-	-	379412^ 479412^	-	-	-	-
96 - 08 4-Runner	6 on 5 1/2	-	-	-	368412^ 468412^	360412^ 460412^	-	-	-	379413	389413^	-	329413^	-

All Classic II and Classic Lock Wheels use standard 'bulge' acorn lug nuts (conical seat). Mickey Thompson Performance Tires & Wheels recommends duplex 'bulge' acorns on vehicles with GVWR of 6500lbs or greater.

Footnotes:

- * = Hub centric application - wheel includes fitment ring.
- ** = Hub centric factory recommended - wheel will be centered on lug nuts.
- *** = Caps included may not fit some Toyota center hubs.

- ^ = Included hub centering ring is not needed for this application, please discard.
Included center cap will not work on manual hub applications.
- # = Some 3/4 ton and 1 ton vehicles use extra long center caps, we recommend using the M/T optional aluminum caps (sold separately).

NOTES

All specifications subject to change without notice. Not responsible for typographical errors.

www.mickeythompson tires.com

Mickey Thompson
Performance Tires & Wheels
4600 Prosper Drive, Stow, OH 44224
PH. (330) 928-9092 • FAX (330) 928-0503

